

NAME

svn cat — Output the content of specified files or URLs

SYNOPSIS

```
svn cat [ --config-dir DIR ] [ --config-option OPT ] [ --no-auth-cache ]
        [ --non-interactive ] [ --password PWD ] [ { -r | --revision } REV ]
        [ --trust-server-cert ] [ --username USR ] TARGET[@REV] ...
```

DESCRIPTION

If specified, *REV* determines in which revision the target is first looked up.

OPTIONS

-r --revision REV the revision argument *REV* can be one of:

<i>NUMBER</i>	revision number
{ ' <i>DATE</i> ' }	revision at start of the date
HEAD	latest in repository
BASE	base rev of item's working copy
COMMITTED	last commit at or before BASE
PREV	revision just before COMMITTED

Some commands also take an *ARG1* : *ARG2* range.

GLOBAL OPTIONS

--config-dir DIR read user configuration files from directory *DIR*

--config-option OPT set user configuration option *OPT* in the format:
 FILE:SECTION:OPTION=[VALUE]
 For example:
 servers:global:http-library=serf

--no-auth-cache do not cache authentication tokens

--non-interactive do no interactive prompting

--password PWD specify a password *PWD*

--trust-server-cert accept unknown SSL server certificates without prompting (but only with **--non-interactive**)

--username USR specify a username *USR*