

NAME

svn move — Move or rename something in working copy or repository

SYNOPSIS

```
svn move (mv, rename, ren) [ -Fmq] [ --config-dir DIR] [ --config-option OPT]
[ --editor-cmd CMD] [ --encoding ENC] [ --file] [ --force]
[ --force-log] [ --message] [ --no-auth-cache] [ --non-interactive]
[ --parents] [ --password PWD] [ --quiet] [{ -r | --revision} REV]
[ --trust-server-cert] [ --username USR] [ --with-revprop PROP] SRC
... DST
```

DESCRIPTION**NOTE**

svn move is equivalent to a **svn copy** followed by **svn delete**.

SRC and *DST* can both be working copy paths or URLs:

WC -> WC move and schedule for addition (with history)

URL -> URL complete server-side rename

All SRCs must be of the same type.

When moving multiple sources, they are added as children of *DST*, which must be a directory.

OPTIONS

--editor-cmd <i>CMD</i>	use <i>CMD</i> as external editor
--encoding <i>ENC</i>	treat value as being in charset encoding <i>ENC</i>
-F --file <i>FIL</i>	read log message from file <i>FIL</i>
--force	force operation to run
--force-log	force validity of log message source
-m --message <i>MSG</i>	specify log message <i>MSG</i>
--parents	make intermediate directories
-q --quiet	print nothing, or only summary information
-r --revision <i>REV</i>	the revision argument <i>REV</i> can be one of: <i>NUMBER</i> revision number ' <i>{</i> <i>DATE</i> <i>}</i> ' revision at start of the date HEAD latest in repository BASE base rev of item's working copy COMMITTED last commit at or before BASE PREV revision just before COMMITTED Some commands also take an <i>ARG1</i> : <i>ARG2</i> range.
--with-revprop <i>PROP</i>	set revision property <i>PROP</i> in a new revision using the <i>name</i> [= <i>value</i>] format

GLOBAL OPTIONS

--config-dir <i>DIR</i>	read user configuration files from directory <i>DIR</i>
--config-option <i>OPT</i>	set user configuration option <i>OPT</i> in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
--no-auth-cache	do not cache authentication tokens

--non-interactive do no interactive prompting
--password *PWD* specify a password *PWD*
--trust-server-cert accept unknown SSL server certificates without prompting (but only with
--non-interactive)
--username *USR* specify a username *USR*

NOTE

The **--revision** option has no use and is deprecated.