

NAME

svn resolved — Remove 'conflicted' state on working copy files or directories

SYNOPSIS

```
svn resolved [-qR] [--config-dir DIR] [--config-option OPT] [--depth DEP]
              [--no-auth-cache] [--non-interactive] [--password PWD]
              [--quiet] [--recursive] [--targets] [--trust-server-cert]
              [--username USR] PATH . . .
```

DESCRIPTION

svn resolved has been deprecated in favor of running

svn resolve --accept working.

svn resolved does *not* semantically resolve conflicts or remove conflict markers. It merely removes the conflict-related artifact files and allows *PATH* to be committed again.

OPTIONS

--depth DEP	limit operation by depth <i>ARG</i> , one of: empty files immediates infinity
-q --quiet	print nothing, or only summary information
-R --recursive	descend recursively, same as --depth=infinity
--targets	pass contents of file <i>ARG</i> as additional arguments

GLOBAL OPTIONS

--config-dir DIR	read user configuration files from directory <i>DIR</i>
--config-option OPT	set user configuration option <i>OPT</i> in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
--no-auth-cache	do not cache authentication tokens
--non-interactive	do no interactive prompting
--password PWD	specify a password <i>PWD</i>
--trust-server-cert	accept unknown SSL server certificates without prompting (but only with --non-interactive)
--username USR	specify a username <i>USR</i>