

NAME

svn delete — Remove files and directories from version control

SYNOPSIS

```
svn delete (del, remove, rm) [ -Fmq] [ --config-dir DIR] [ --config-option OPT]
    [ --editor-cmd CMD] [ --encoding ENC] [ --file] [ --force]
    [ --force-log] [ --keep-local] [ --message] [ --no-auth-cache]
    [ --non-interactive] [ --password PWD] [ --quiet] [ --targets]
    [ --trust-server-cert] [ --username USR] [ --with-revprop PROP]
    {PATH ... | URL ...}
```

DESCRIPTION

Each item specified by a *PATH* is scheduled for deletion upon the next commit. Files, and directories that have not been committed, are immediately removed from the working copy unless the **--keep-local** option is given. *PATHs* that are, or contain, unversioned or modified items will not be removed unless the **--force** option is given.

Each item specified by a *URL* is deleted from the repository via an immediate commit.

OPTIONS

--editor-cmd <i>CMD</i>	use <i>CMD</i> as external editor
--encoding <i>ENC</i>	treat value as being in charset encoding <i>ENC</i>
-F --file <i>FIL</i>	read log message from file <i>FIL</i>
--force	force operation to run
--force-log	force validity of log message source
--keep-local	keep path in working copy
-m --message <i>MSG</i>	specify log message <i>MSG</i>
-q --quiet	print nothing, or only summary information
--targets	pass contents of file <i>ARG</i> as additional arguments
--with-revprop <i>PROP</i>	set revision property <i>PROP</i> in a new revision using the <i>name[=value]</i> format

GLOBAL OPTIONS

--config-dir <i>DIR</i>	read user configuration files from directory <i>DIR</i>
--config-option <i>OPT</i>	set user configuration option <i>OPT</i> in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
--no-auth-cache	do not cache authentication tokens
--non-interactive	do no interactive prompting
--password <i>PWD</i>	specify a password <i>PWD</i>
--trust-server-cert	accept unknown SSL server certificates without prompting (but only with --non-interactive)
--username <i>USR</i>	specify a username <i>USR</i>