

NAME

svn add — Put files and directories under version control

SYNOPSIS

```
svn add [-Nq] [--auto-props] [--config-dir DIR] [--config-option OPT]
        [--depth DEP] [--force] [--non-recursive] [--no-auth-cache]
        [--no-auto-props] [--no-ignore] [--non-interactive] [--parents]
        [--password PWD] [--quiet] [--targets] [--trust-server-cert]
        [--username USR] PATH ...
```

DESCRIPTION

Scheduling files for addition to repository. They will be added in next commit.

OPTIONS

--auto-props	enable automatic properties
--depth DEP	limit operation by depth <i>ARG</i> , one of: empty files immediates infinity
--force	force operation to run
-N --non-recursive	obsolete; try --depth=files or --depth=immediates
--no-auto-props	disable automatic properties
--no-ignore	disregard default and svn:ignore property ignores
--parents	add intermediate parents
-q --quiet	print nothing, or only summary information
--targets	pass contents of file <i>ARG</i> as additional arguments

GLOBAL OPTIONS

--config-dir DIR	read user configuration files from directory <i>DIR</i>
--config-option OPT	set user configuration option <i>OPT</i> in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
--no-auth-cache	do not cache authentication tokens
--non-interactive	do no interactive prompting
--password PWD	specify a password <i>PWD</i>
--trust-server-cert	accept unknown SSL server certificates without prompting (but only with --non-interactive)
--username USR	specify a username <i>USR</i>