

NAME

svn changelist — Associate changelist with files

SYNOPSIS

```
svn changelist (cl) [-qR] [--changelist CHG] [--cl] [--config-dir DIR]
                    [--config-option OPT] [--depth DEP] [--no-auth-cache]
                    [--non-interactive] [--password PWD] [--quiet]
                    [--recursive] [--remove] [--targets] [--trust-server-cert]
                    [--username USR] CLNAME TARGET ...

svn changelist --remove TARGET ...
```

DESCRIPTION

Associate (or dissociate) changelist *CLNAME* with the named files.

OPTIONS

--changelist --cl <i>CHG</i>	operate only on members of changelist <i>CHG</i>
--depth <i>DEP</i>	limit operation by depth <i>ARG</i> , one of: empty files immediates infinity
-q --quiet	print nothing, or only summary information
-R --recursive	descend recursively, same as --depth=infinity
--remove	remove changelist association
--targets	pass contents of file <i>ARG</i> as additional arguments

GLOBAL OPTIONS

--config-dir <i>DIR</i>	read user configuration files from directory <i>DIR</i>
--config-option <i>OPT</i>	set user configuration option <i>OPT</i> in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
--no-auth-cache	do not cache authentication tokens
--non-interactive	do no interactive prompting
--password <i>PWD</i>	specify a password <i>PWD</i>
--trust-server-cert	accept unknown SSL server certificates without prompting (but only with --non-interactive)
--username <i>USR</i>	specify a username <i>USR</i>