

**NAME**

**svn info** — Display information about a local or remote item

**SYNOPSIS**

```
svn info [-R] [--changelist CHG] [--cl] [--config-dir DIR]
          [--config-option OPT] [--depth DEP] [--incremental]
          [--no-auth-cache] [--non-interactive] [--password PWD]
          [{-r | --revision} REV] [--recursive] [--targets]
          [--trust-server-cert] [--username USR] [--xml] [TARGET[@REV] ...]
```

**DESCRIPTION**

Print information about each *TARGET* (default: '.'). *TARGET* may be either a working-copy path or URL. If specified, *REV* determines in which revision the target is first looked up.

**OPTIONS**

<b>--changelist</b>	<b>--cl</b>	<i>CHG</i>	operate only on members of changelist <i>CHG</i>
<b>--depth</b>	<i>DEP</i>		limit operation by depth <i>ARG</i> , one of: empty files immediates infinity
<b>--incremental</b>			give output suitable for concatenation
<b>-r</b>	<b>--revision</b>	<i>REV</i>	the revision argument <i>REV</i> can be one of: <i>NUMBER</i> revision number '{' <i>DATE</i> '}'      revision at start of the date HEAD              latest in repository BASE              base rev of item's working copy COMMITTED        last commit at or before BASE PREV              revision just before COMMITTED
<b>-R</b>	<b>--recursive</b>		Some commands also take an <i>ARG1</i> : <i>ARG2</i> range. descend recursively, same as <b>--depth=infinity</b>
<b>--targets</b>			pass contents of file <i>ARG</i> as additional arguments
<b>--xml</b>			output in XML

**GLOBAL OPTIONS**

<b>--config-dir</b>	<i>DIR</i>	read user configuration files from directory <i>DIR</i>
<b>--config-option</b>	<i>OPT</i>	set user configuration option <i>OPT</i> in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
<b>--no-auth-cache</b>		do not cache authentication tokens
<b>--non-interactive</b>		do no interactive prompting
<b>--password</b>	<i>PWD</i>	specify a password <i>PWD</i>
<b>--trust-server-cert</b>		accept unknown SSL server certificates without prompting (but only with <b>--non-interactive</b> )
<b>--username</b>	<i>USR</i>	specify a username <i>USR</i>