

NAME

svn resolve — Resolve conflicts on working copy files or directories

SYNOPSIS

```
svn resolve [-qR] [--accept] [--config-dir DIR] [--config-option OPT]
            [--depth DEP] [--no-auth-cache] [--non-interactive]
            [--password PWD] [--quiet] [--recursive] [--targets]
            [--trust-server-cert] [--username USR]
            --accept ARG [PATH ...]
```

DESCRIPTION

Note: the **--accept** option is currently required.

OPTIONS

--accept	specify automatic conflict resolution source, one of: base working mine-conflict theirs-conflict mine-full theirs-full
--depth DEP	limit operation by depth ARG, one of: empty files immediates infinity
-q --quiet	print nothing, or only summary information
-R --recursive	descend recursively, same as --depth=infinity
--targets	pass contents of file ARG as additional arguments

GLOBAL OPTIONS

--config-dir DIR	read user configuration files from directory DIR
--config-option OPT	set user configuration option OPT in the format: FILE:SECTION:OPTION=[VALUE] For example: servers:global:http-library=serf
--no-auth-cache	do not cache authentication tokens
--non-interactive	do no interactive prompting
--password PWD	specify a password PWD
--trust-server-cert	accept unknown SSL server certificates without prompting (but only with --non-interactive)
--username USR	specify a username USR